

Bid #: 26-049

Project: Automotive 12VT BatteriesDepartment: FleetDate: 09/23/2026Time: 2:00 P.M. CST**Bidder Name****Bidder #**

|                     |                  |                     |  |  |
|---------------------|------------------|---------------------|--|--|
| Parts Authority LLC | Alapa Auto Parts | Wholesale Batteries |  |  |
| 1                   | 2                | 3                   |  |  |

**Vendor Price 4th Qtr 2026****Unit Price**

| Line | Battery Group / Type                               | Minimum Specification | Technology                 |        |        |        |  |  |
|------|----------------------------------------------------|-----------------------|----------------------------|--------|--------|--------|--|--|
| 1    | Group 65 top post                                  | 12V; 750 CCA minimum  | Maintenance-Free / Flooded | 111.35 | 96.99  | 116.23 |  |  |
| 1a   | Group 65 (If applicable) threaded stud mount       | 12V; 750 CCA minimum  | Maintenance-Free / Flooded | —      | —      | —      |  |  |
| 1b   | Group 65 (If applicable) dual terminal mount       | 12V; 750 CCA minimum  | Maintenance-Free / Flooded | —      | —      | —      |  |  |
|      |                                                    |                       |                            |        |        |        |  |  |
| 2    | H6 / Group 48 top post                             | 12V; 760 CCA minimum  | AGM                        | 179.68 | 155.00 | 205.08 |  |  |
| 2a   | H6 / Group 48 (If applicable) threaded stud mount  | 12V; 760 CCA minimum  | AGM                        | —      | —      | —      |  |  |
| 2b   | H6 / Group 48 (If applicable) dual terminal mount  | 12V; 760 CCA minimum  | AGM                        | —      | —      | —      |  |  |
|      |                                                    |                       |                            |        |        |        |  |  |
| 3    | H7 / Group 94R top post                            | 12V; 850 CCA minimum  | AGM                        | 187.69 | 155.00 | 180.51 |  |  |
| 3a   | H7 / Group 94R (If applicable) threaded stud mount | 12V; 850 CCA minimum  | AGM                        | —      | —      | —      |  |  |

Initials

Bid 26-049


|    |                                                    |                                  |                                                   |        |        |        |  |
|----|----------------------------------------------------|----------------------------------|---------------------------------------------------|--------|--------|--------|--|
| 3b | H7 / Group 94R (If applicable) dual terminal mount | 12V; 850 CCA minimum             | AGM                                               | -      | -      | -      |  |
| 4  | H8 / Group 49 top post                             | 12V; 900 CCA minimum             | AGM                                               | 203.71 | 155.00 | 226.94 |  |
| 4a | H8 / Group 49 (if applicable) threaded stud mount  | 12V; 900 CCA minimum             | AGM                                               | -      | -      | -      |  |
| 4b | H8 / Group 49 (if applicable) dual terminal mount  | 12V; 900 CCA minimum             | AGM                                               | -      | -      | -      |  |
| 5  | Group 31 top post                                  | 12V; 950 CCA minimum; Heavy-Duty | Heavy-Duty Commercial                             | 120.60 | 115.00 | 124.81 |  |
| 5a | Group 31 (If applicable) threaded stud mount       | 12V; 950 CCA minimum; Heavy-Duty | Heavy-Duty Commercial                             | -      | 115.00 | 124.81 |  |
| 5b | Group 31 (If applicable) dual terminal mount       | 12V; 950 CCA minimum; Heavy-Duty | Heavy-Duty Commercial                             | -      | -      | -      |  |
| 6  | Group 24 / 24F top post                            | 12V; 750 CCA minimum             | Maintenance-Free / Flooded                        | 99.71  | 96.99  | 123.04 |  |
| 6a | Group 24 / 24F (If applicable) threaded stud mount | 12V; 750 CCA minimum             | Maintenance-Free / Flooded                        | -      | -      | -      |  |
| 6b | Group 24 / 24F (If applicable) dual terminal mount | 12V; 750 CCA minimum             | Maintenance-Free / Flooded                        | -      | -      | -      |  |
| 7  | 96R / H5 top post                                  | 12V; 650 CCA minimum             | Maintenance-Free / AGM as required by application | 96.19  | 96.99  | 323.69 |  |
| 7a | 96R / H5 (If applicable) threaded stud mount       | 12V; 650 CCA minimum             | Maintenance-Free / AGM as required by application | -      | -      | -      |  |
| 7b | 96R / H5 (If applicable) dual terminal mounted     | 12V; 650 CCA minimum             | Maintenance-Free / AGM as required by application | -      | -      | -      |  |

Initials

Bid 26-049

| Vendor Price 2027 |                                                    |                       |                            | Unit Price |        |        |  |  |
|-------------------|----------------------------------------------------|-----------------------|----------------------------|------------|--------|--------|--|--|
| Line              | Battery Group / Type                               | Minimum Specification | Technology                 |            |        |        |  |  |
| 1                 | Group 65 top post                                  | 12V; 750 CCA minimum  | Maintenance-Free / Flooded | 104.39     | 102.38 | 122.05 |  |  |
| 1a                | Group 65 (If applicable) threaded stud mount       | 12V; 750 CCA minimum  | Maintenance-Free / Flooded | -          | -      | -      |  |  |
| 1b                | Group 65 (If applicable) dual terminal mount       | 12V; 750 CCA minimum  | Maintenance-Free / Flooded | -          | -      | -      |  |  |
|                   |                                                    |                       |                            |            |        |        |  |  |
| 2                 | H6 / Group 48 top post                             | 12V; 760 CCA minimum  | AGM                        | 185.07     | 163.60 | 215.33 |  |  |
| 2a                | H6 / Group 48 (If applicable) threaded stud mount  | 12V; 760 CCA minimum  | AGM                        | -          | -      | -      |  |  |
| 2b                | H6 / Group 48 (If applicable) dual terminal mount  | 12V; 760 CCA minimum  | AGM                        | -          | -      | -      |  |  |
|                   |                                                    |                       |                            |            |        |        |  |  |
| 3                 | H7 / Group 94R top post                            | 12V; 850 CCA minimum  | AGM                        | 193.32     | 163.60 | 189.54 |  |  |
| 3a                | H7 / Group 94R (If applicable) threaded stud mount | 12V; 850 CCA minimum  | AGM                        | -          | -      | -      |  |  |
| 3b                | H7 / Group 94R (If applicable) dual terminal mount | 12V; 850 CCA minimum  | AGM                        | -          | -      | -      |  |  |
|                   |                                                    |                       |                            |            |        |        |  |  |

Initials



|    |                                                    |                                  |                                                   |        |        |        |  |
|----|----------------------------------------------------|----------------------------------|---------------------------------------------------|--------|--------|--------|--|
| 4  | H8 / Group 49 top post                             | 12V; 900 CCA minimum             | AGM                                               | 209.82 | 163.00 | 238.29 |  |
| 4a | H8 / Group 49 (if applicable) threaded stud mount  | 12V; 900 CCA minimum             | AGM                                               | -      | -      | -      |  |
| 4b | H8 / Group 49 (if applicable) dual terminal mount  | 12V; 900 CCA minimum             | AGM                                               | -      | -      | -      |  |
|    |                                                    |                                  |                                                   |        |        |        |  |
| 5  | Group 31 top post                                  | 12V; 950 CCA minimum; Heavy-Duty | Heavy-Duty Commercial                             | 124.22 | 121.00 | 131.05 |  |
| 5a | Group 31 (If applicable) threaded stud mount       | 12V; 950 CCA minimum; Heavy-Duty | Heavy-Duty Commercial                             | -      | 121.00 | 131.05 |  |
| 5b | Group 31 (If applicable) dual terminal mount       | 12V; 950 CCA minimum; Heavy-Duty | Heavy-Duty Commercial                             | -      | -      | -      |  |
|    |                                                    |                                  |                                                   |        |        |        |  |
| 6  | Group 24 / 24F top post                            | 12V; 750 CCA minimum             | Maintenance-Free / Flooded                        | 102.70 | 102.38 | 129.22 |  |
| 6a | Group 24 / 24F (If applicable) threaded stud mount | 12V; 750 CCA minimum             | Maintenance-Free / Flooded                        | -      | -      | -      |  |
| 6b | Group 24 / 24F (If applicable) dual terminal mount | 12V; 750 CCA minimum             | Maintenance-Free / Flooded                        | -      | -      | -      |  |
|    |                                                    |                                  |                                                   |        |        |        |  |
| 7  | 96R / H5 top post                                  | 12V; 650 CCA minimum             | Maintenance-Free / AGM as required by application | 99.08  | 102.38 | 339.87 |  |
| 7a | 96R / H5 (If applicable) threaded stud mount       | 12V; 650 CCA minimum             | Maintenance-Free / AGM as required by application | -      | -      |        |  |
| 7b | 96R / H5 (If applicable) dual terminal mounted     | 12V; 650 CCA minimum             | Maintenance-Free / AGM as required by application | -      | -      |        |  |

*Shawn M. New*, Purchasing Agent

Initials *HN*